

Sustainability data sheet

ARDEX S 1-K Sealing compound

One-compound sealant for sealing under tiles and panels.

Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf)

EMICODE® EC 1,
very low emission



According Emission Classification of Building Materials

-

According eco-bau

eco-1



solvent-free

EPD (Environmental Product Declaration)

ARDEX S 1-K corresponds to FEICA EPD:

-

According BASTA

ARDEX S 1-K is BASTA registered.

BASTA registration means that we can verify that this product meets agreed properties criteria regarding properties hazardous to the environment and health. See www.bastaonline.se



Technical Assessment

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):

GISCODE (acrylate dispersion): D1 – solvent-free dispersion installation products

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



ARDEX S 1-K

Sealing compound

Sustainable Building

Accordinging DGNB (German Sustainable Building Council)

Version 2023

DGNB criteria ENV 1.2: Local environmental impact

ARDEX S 1-K can be categorized under Sealing coats, screed resins, waterproofing under tiles. ARDEX S 1-K has the GISOCDE D1 and is certified by EMICODE® EC 1^{PLUS}, very low emission, based on GEV.

ARDEX X 701 F fulfils the requirements for highest Quality Level 4.

Accordinging LEED (Leadership in Energy and Environmental Design)

Version 4 (2014)

EQ: Low Emitting Materials

ARDEX S 1-K meets the requirements according EMICODE® EC 1, very low emission, based on GEV which are accepted by LEED.

ARDEX S 1-K meets the requirements and contributes to achieving one LEED point under EQ: Low Emitting Materials.

MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX S 1-K corresponds to no model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

ARDEX S 1-K does not meet the requirements.

Version 2009

IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

The permitted limit value in the category Sealants - other Sealant according SCAQMD Rule 1168 is 420 g/L. The VOC value of ARDEX S 1-K according SCAQMD Rule 1168 is < 420 g/L.

ARDEX S 1-K meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.

MR Credit 5.1 und 5.2: Regional Materials

Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

Accordinging BREEAM-NOR (Building Research Establishment Environmental Assessment Methodology)

Version 2016

BREEAM-NOR criteria Hea 02 Indoor air quality

ARDEX S 1-K can be classified as Sealants like elastic or plastic sealants bases on polyurethane, silicone, MS, acrylic or other.

ARDEX S 1-K fulfils the required emission limits and is certified by EMICODE® EC 1, very low emission, based on GEV which is accepted as documentation.

ARDEX S 1-K meets the requirements according BREEAM-NOR and contributes to achieving one credit under Hea 02 Indoor air quality.

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



ARDEX S 1-K

Sealing compound

According BREEAM (Building Research Establishment Environmental Assessment Methodology)

Version 2016

BREEAM criteria Hea 02 Indoor air quality

ARDEX S 1-K can be classified as Interior adhesives and sealants (including flooring adhesives). ARDEX S 1-K meets the requirements according Table 17: Emission criteria by product type and Table 18: Exemplary level emission criteria by product type.

ARDEX S 1-K is certified by EMICODE® EC 1, very low emission, based on GEV.

ARDEX S 1-K meets the requirements according BREEAM and contributes to achieving one credit under Hea 02 Indoor air quality.

According Nordic Swan Ecolabelling

ARDEX S 1-K is listed in the database for building products that can be used in Nordic Swan Eco labelled buildings.

Notice: This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship. Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH
Witten, 08/07/2024

ARDEX GmbH
Friedrich-Ebert-Straße 45
58453 Witten
www.ardex.de

Tel.: +49 2302 664-511
Fax: +49 2302 664-298
kundendienst@ardex.de
www.ardex.de

