

Sustainability data sheet

ARDEX X 701 F Flexible Tile Adhesive

Installation and laying of tiles based on stoneware and fine stoneware, glass mosaic and porcelain, artificial stone panels and moisture resistant nature stone panels. In- and outdoors, floor.

Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf)

EMICODE® EC 1^{PLUS},
very low emission



solvent-free

EPD (Environmental Product Declaration)

ARDEX X 701 F corresponds to FEICA EPD:

EPD-DBC-20220217-IBF1-EN

According BASTA

ARDEX X 701 F is BASTA registered.

BASTA registration means that we can verify that this product meets agreed properties criteria regarding properties hazardous to the environment and health. See www.bastaonline.se



Technical Assessment

Meets the C2 requirements according to EN 12004

C2 TE, Cement mortar for increased requirements with additional characteristic values extended open time (E) and reduced slipping (T).

Meets the S1 requirements according to EN 12002

S1 deformability > 2,5 mm

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):
GISCODE ZP1 - cementitious product, low-chromate

ARDEX GmbH
Friedrich-Ebert-Straße 45
58453 Witten
www.ardex.de

Tel.: +49 2302 664-511
Fax: +49 2302 664-298
kundendienst@ardex.de
www.ardex.de



Sustainable Building

Accordinging DGNB (German Sustainable Building Council)

Version 2023

DGNB criteria ENV 1.2: Local environmental impact

ARDEX 701 F can be categorized under Primers, undercoats, fillers and adhesives under wall and floor coverings (e.g. tiles, carpets, parquet, elastic flooring – except for wallpaper). ARDEX X 701 F has the GISOCDE P1 and is certified by EMICODE® EC 1^{PLUS}, very low emission, based on GEV.

ARDEX X 701 F fulfils the requirements for highest Quality Level 4.

Accordinging LEED (Leadership in Energy and Environmental Design)

Version 4 (2014)

EQ: Low Emitting Materials

ARDEX X 701 F meets the requirements according EMICODE® EC 1^{PLUS}, very low emission, based on GEV which are accepted by LEED.

ARDEX X 701 F meets the requirements and contributes to achieving one LEED point under EQ: Low Emitting Materials.

MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX X 701 F corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate “.

ARDEX X 701 F fulfils the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.

Version 2009

IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

The permitted limit value in the category primers, sealings and undercoatings according SCAQMD Rule 1168 is 65 g/L. The VOC value of ARDEX X 701 F according SCAQMD Rule 1168 is < 65 g/L.

ARDEX X 701 F meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.

MR Credit 5.1 und 5.2: Regional Materials

Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometres) can be contributed to achieving one LEED point.

Accordinging BREEAM-NOR (Building Research Establishment Environmental Assessment Methodology)

Version 2016

BREEAM-NOR criteria Hea 02 Indoor air quality

ARDEX X 701 F fulfils the required emission limits and is certified by EMICODE® EC 1^{PLUS}, very low emission, based on GEV which is accepted as documentation.

ARDEX X 701 F meets the requirements according BREEAM-NOR and contributes to achieving one credit under Hea 02 Indoor air quality.

ARDEX GmbH
Friedrich-Ebert-Straße 45
58453 Witten
www.ardex.de

Tel.: +49 2302 664-511
Fax: +49 2302 664-298
kundendienst@ardex.de
www.ardex.de



ARDEX X 701 F

Flexible Tile Adhesive

Accordinging Nordic Swan Ecolabelling

ARDEX X 701 F is listed in the database for building products that can be used in Nordic Swan Eco labelled buildings.

Notice: This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship. Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH
Witten, 08/07/2024

ARDEX GmbH
Friedrich-Ebert-Straße 45
58453 Witten
www.ardex.de

Tel.: +49 2302 664-511
Fax: +49 2302 664-298
kundendienst@ardex.de
www.ardex.de

