LOBADUR®

FactoryBase

Water-based roller primer for cement-based levelling compounds for direct use.

Emissions

EMISSION CLASS FOR BUILDING MATERIAL · RTS · M1	Harmless according to expert evaluation of VOC, ingredients and odour	According to RTS (Building Information Foundation Finland)

Technical evaluation

2004/42/CE	EU limit value for this product (cat. A/i): 140 g/l (2010). , This product contains max. 51 g/l VOC.
GISCODE	W2+ (Water-thinnable surface treatment agents, solvent content up to 5%, N-methylpyrrolidone free)

Glossar

M1

The M 1 classification is part of the voluntary Finnish indoor climate classification system. It is published by the Finnish Association for Indoor Air and Climate (FiSIAQ).

2004/42/CE

The "Decopaint-Directive" is a limitation of volatile organic compounds (VOC)* proclaimed by the EU due to the use of organic solvents in certain paints and varnishes.

GISCODE

The term GISCODE stands for Hazardous Substance Information System Code and was developed by the BG Bau (Employer's Liability Insurance Association for the Construction Industry). It is a labelling system in which products with comparable health hazards are grouped together in product groups. The coding consists of a letter/number combination that uniquely assigns the product to a product group. To obtain specific product information, a product group can be selected on the GISBAU website (= Hazardous Substance Information System of the BG Bau) and detailed hazardous substance information can be found in the appropriate table.

Notes

Notice

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

11/09/2024

LOBA GmbH & Co. KG | Leonberger Str. 56-62 | 71254 Ditzingen | Germany
Fon: +49 7156 357-0 | Fax: +49 7156 357-211 | service@loba.de | www.loba.de